

POOLMASTER®

We Make Water Fun!

INSTRUCTIONS FOR 2-WAY DPD TEST KIT

Take water samples from depth of 12" to 18" away from return lines. Rinse test vial before each test.

DPD FREE CHLORINE TEST - For amount of Chlorine residual in pool or spa water

1. Fill small test vial to line.
2. Add 1 DPD #1 tablet.
3. Place cap on vial and swirl to mix.
4. Compare color with chlorine standards on left marked in parts per million (ppm). A desirable reading is 2.0 to 3.0. However, additional Chlorine may be needed to maintain a proper level.

pH TEST – For degree of acidity or alkalinity of pool or spa water

1. Fill test vial to pH line.
2. Add 5 drops of Phenol Red solution.
3. Place cap on vial and swirl to mix.
4. Compare color with pH standards on right.
5. A desirable pH reading is 7.2 to 7.6.

CAUTION: MAY CAUSE EYE IRRITATION. MAY BE HARMFUL IF SWALLOWED.



NOTE: The cap must always be used with the test kit vial. Do not cover the test kit vial with fingers during use.

CAUTION: Conduct tests before adding chemicals. Store test kit in a cool, dark place. For accuracy, use fresh solutions at the start of each season.

CAUTION: MAY CAUSE EYE IRRITATION. MAY BE HARMFUL IF SWALLOWED. KEEP OUT OF REACH OF CHILDREN. Avoid eye contact. Contains suspect oral carcinogen. Contains suspect oral reproductive toxin. Wash hands after use. Do not eat, drink, or smoke while using. Keep container closed.

First Aid: If on skin or in eyes, rinse thoroughly with water. Remove contact lenses, if present and easy to do. Continue rinsing. If swallowed or any of the above occurs, contact a physician or Poison Control Center and show this label. **DO NOT INDUCE VOMITING. Contains Boric Acid, Citric Acid, N,N-Diethyl-p-phenylenediamine Sulfate, and Phenol Red.**

Store locked up. Dispose of contents in accordance to applicable law.

24-Hour Emergency – 1-800-255-3924

Poolmaster® Inc.
770 Del Paso Rd.
Sacramento
CA 95834
1-800-854-1492
poolmaster.com

Assembled in USA
with global components